

Safety Data Sheet

1567 PIPE SEALANT

SUR-LOK™

SDS Revision Date:

01/07/2019

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity 1567 PIPE SEALANT
Alternate Names Part Numbers: 15677, 15675
Product Type: Industrial Grade Pipe Sealant

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use See Technical Data Sheet.
Application Method Anaerobic Adhesive/ Sealant

1.3. Details of the supplier of the safety data sheet

Company Name SUR-LOK Corporation
Walworth WI, 53147

Emergency

CHEMTREC (USA) (800) 424-9300
24 hour Emergency Telephone No. (703) 527-3887
Customer Service: SUR-LOK Corporation (888)784-7711

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Skin Irrit. 2;H315 Causes skin irritation.
Eye Irrit. 2;H319 Causes serious eye irritation.
STOT SE 3;H335 May cause respiratory irritation.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Warning

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

[Prevention]:

Safety Data Sheet

1567 PIPE SEALANT

SUR-LOK™

SDS Revision Date:

01/07/2019

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection / face protection.

[Response]:

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P321 Specific treatment (see information on this label).

P337+313 If eye irritation persists: Get medical advice / attention.

P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P362 Take off contaminated clothing and wash before reuse.

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
HEXANOIC ACID, 2-ETHYL-, DIESTER WITH TETRAETHYLEN CAS Number: 0018268-70-7	25 - 50		[1]
Triethylene glycol dimethacrylate CAS Number: 0000109-16-0	10 - 25	Eye Irrit. 2;H319 STOT SE 3;H335 Skin Irrit. 2;H315	[1]
Polyethylene CAS Number: 0009002-88-4	10 - 25		[1]
Ptfe CAS Number: 0009002-84-0	1.0 - 10		[1]
Amorphous fumed silica CAS Number: 0112945-52-5	1.0 - 10		[1]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

Safety Data Sheet

1567 PIPE SEALANT

SUR-LOK™

SDS Revision Date:

01/07/2019

4.1. Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview	<p>Skin Contact: Usually no effect, however, as with any chemical, prolonged, excessive, or repeated exposure may cause mild to moderate skin irritation, exhibited by redness, drying and cracking of unprotected skin.</p> <p>Eye Contact: May irritate with slight pain and redness.</p> <p>Respiratory/ Inhalation: Usually none, however, as with any chemical product, some irritation may occur.</p> <p>Ingestion: Amounts transferred to mouth by fingers, etc, during normal operation should not cause injury.</p> <p>Medical conditions generally aggravated by exposure: None known however any chemical product may enhance allergies already present in certain individuals.</p> <p>See section 2 for further details.</p>
Eyes	Causes serious eye irritation.
Skin	Causes skin irritation.

5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Oxides of carbon and nitrogen.

Avoid breathing dust / fume / gas / mist / vapors / spray.

5.3. Advice for fire-fighters

Air mask and procedures for fighting chemical fires. Do not inhale gases.

Safety Data Sheet

1567 PIPE SEALANT

SUR-LOK™

SDS Revision Date:

01/07/2019

ERG Guide No. ----

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Prevent material from entering floor drains, sewers, or any bodies of water.

Scoop up into waste container or soak up with absorbent material. Store in a closed container until disposal.

7. Handling and storage

7.1. Precautions for safe handling

Avoid breathing vapors. Wash hands thoroughly at mealtime and end of shift. Wear personal protective equipment as outlined in Section 8 of this SDS.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Isolated storage facility/ warehouse not required. Store in a cool, dry location (60-90°F) in a well-ventilated area in original container. Keep container tightly closed when not in use.

Incompatible materials: Reducing agents. Strong oxidizers.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

None

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000109-16-0	Triethylene glycol dimethacrylate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0009002-84-0	Ptfe	OSHA	No Established Limit

Safety Data Sheet
1567 PIPE SEALANT



SDS Revision Date:

01/07/2019

		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0009002-88-4	Polyethylene	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0018268-70-7	HEXANOIC ACID, 2-ETHYL-, DIESTER WITH TETRAETHYLEN	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0112945-52-5	Amorphous fumed silica	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000109-16-0	Triethylene glycol dimethacrylate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0009002-84-0	Ptfе	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0009002-88-4	Polyethylene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0018268-70-7	HEXANOIC ACID, 2-ETHYL-, DIESTER WITH TETRAETHYLEN	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0112945-52-5	Amorphous fumed silica	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory

No respiratory protection required, but normal good ventilation is recommended. Forced ventilation may be required if concentrations exceed normal use exposure.

Eyes

Safety goggles or glasses are recommended.

Skin

Use impermeable gloves (neoprene, butyl rubber, natural rubber), as necessary to avoid skin contact, as well as proper clothing or plastic apron. Wash hands before eating, drinking, or using restroom.

Safety Data Sheet

1567 PIPE SEALANT

SUR-LOK™

SDS Revision Date:

01/07/2019

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices Eye wash stations should be located within 100 feet or 10 second walk of the work area. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance	White Creamy Paste
Odor	Mild
Odor threshold	Not Measured
pH	N/A
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	>300 F
Flash Point	200 F (T.C.C.)
Evaporation rate (Ether = 1)	N/A
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: N/A
	Upper Explosive Limit: N/A
Vapor pressure (Pa)	< 5 @80 F (mm Hg.)
Vapor Density	N/A
Specific Gravity	1.05
Solubility in Water	Partial
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
VOC %	<0.1%

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

Safety Data Sheet
1567 PIPE SEALANT



SDS Revision Date:

01/07/2019

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

Reducing agents. Strong oxidizers.

10.6. Hazardous decomposition products

Oxides of carbon and nitrogen.

11. Toxicological information

Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
HEXANOIC ACID, 2-ETHYL-, DIESTER WITH TETRAETHYLEN - (18268-70-7)	No data available	No data available	No data available	No data available	No data available
Triethylene glycol dimethacrylate - (109-16-0)	10,837.00, Rat - Category: NA	No data available	No data available	No data available	No data available
Polyethylene - (9002-88-4)	No data available	No data available	No data available	No data available	No data available
Ptfe - (9002-84-0)	No data available	No data available	No data available	No data available	No data available
Amorphous fumed silica - (112945-52-5)	3,160.00, Rat - Category: 5	No data available	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable

Safety Data Sheet
1567 PIPE SEALANT



SDS Revision Date:

01/07/2019

Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
HEXANOIC ACID, 2-ETHYL-, DIESTER WITH TETRAETHYLEN - (18268-70-7)	Not Available	Not Available	Not Available
Triethylene glycol dimethacrylate - (109-16-0)	Not Available	Not Available	Not Available
Polyethylene - (9002-88-4)	Not Available	Not Available	Not Available
Ptfe - (9002-84-0)	Not Available	Not Available	Not Available
Amorphous fumed silica - (112945-52-5)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

Safety Data Sheet
1567 PIPE SEALANT



SDS Revision Date:

01/07/2019

14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable	Not Regulated	Not Regulated
14.2. UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
14.3. Transport hazard class(es)	DOT Hazard Class: Not Applicable DOT Label: ---	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazards			
IMDG	Marine Pollutant: No		
14.6. Special precautions for user	No further information		

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA Inventory.

WHMIS Classification D2B

US EPA Tier II Hazards

Fire: No
Sudden Release of Pressure: No
Reactive: No
Immediate (Acute): Yes
Delayed (Chronic): No

EPCRA 311/312 Chemicals and RQs:
 (No Product Ingredients Listed)

EPCRA 302 Extremely Hazardous :
 (No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals:
 (No Product Ingredients Listed)

Proposition 65 - Carcinogens (>0.0%):
 (No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0.0%):
 (No Product Ingredients Listed)

Proposition 65 - Female Repro Toxins (>0.0%):
 (No Product Ingredients Listed)

Safety Data Sheet

1567 PIPE SEALANT

SUR-LOK™

SDS Revision Date:

01/07/2019

Proposition 65 - Male Repro Toxins (>0.0%):

(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :

(No Product Ingredients Listed)

Penn RTK Substances (>1%):

Ptfe

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

The information on this material safety data sheet represents our current data and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or which involves using the product in combination with any other product or any other process is the responsibility of the user. SUR-LOK Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of SUR-LOK Corporation products.

End of Document